

AMPED I Volume 2

5mm Luxury Vinyl Plank

Classification	ASTM F-3261-17, Resilient flooring in modular format with Solid Polymeric Core	Packaging	18.91 ft ² (1.76 m ²) per carton 8 pieces per carton 60 cartons per pallet
Plank Size	7" x 48" / 180 mm x 1220 mm (nom)	Weight Per Carton	32.43 lbs / 14.71 kg
Overall Thickness	0.16" / 5 mm (4 mm + 1 mm cushion backing)		
Wear Layer	6 mil / 0.15 mm		
Edge	Square		
Colors	6 standard colors		
Finish	Superior Coating		
Warranty	20 Year Residential / 10 Year Light Commercial		

Product Testing

Size and Tolerance	ISO 24337	Passes
Residual Indentation	ASTM F 1914	Passes
Dimensional Stability	ISO 23999	Passes
Thickness	ASTM F 387	Passes
Static Load Limit	ASTM F 970	Passes
Chemical Resistance	ASTM F 925	Passes
Smoke Density	ASTM E 662	Passes
Critical Radiant Flux	ASTM E 648	Passes
Static Coefficient of Friction	ASTM C 1028	Passes
STC Sound Testing	ASTM 492-09	62
IIC Sound Testing	ASTM E 989-06	71

AMPED I Volume 3

5mm Luxury Vinyl Plank

Classification	ASTM F-3261-17, Resilient flooring in modular format with Solid Polymeric Core	Packaging	21.95 ft ² (2.04 m ²) per carton 6 pieces per carton 68 cartons per pallet
Plank Size	9" x 60" (nom) / 223 mm x 1524 mm		
Overall Thickness	0.16" / 5 mil	Weight Per Carton	37.75 lbs / 17.12 kg
Wear Layer	5 mm / 0.30 mm (4 mm + 1 mm cushion backing)		
Edge	Bevel		
Colors	6 standard colors		
Finish	Superior Coating		
Warranty	20 Year Residential / 10 Year Light Commercial		

Product Testing

Size and Tolerance	ISO 24337	Passes
Residual Indentation	ASTM F 1914	Passes
Dimensional Stability	ISO 23999	Passes
Thickness	ASTM F 387	Passes
Static Load Limit	ASTM F 970	Passes
Chemical Resistance	ASTM F 925	Passes
Smoke Density	ASTM E 662	Passes
Critical Radiant Flux	ASTM E 648	Passes
Static Coefficient of Friction	ASTM C 1028	Passes
STC Sound Testing	ASTM 492-09	62
IIC Sound Testing	ASTM E 989-06	71