

## Melodies<sup>TM</sup>

## 3mm Luxury Vinyl Tile

<b>General Testing Standard</b>	ASTM F-1700, Class III, Type B	<b>Packaging</b>	36 ft <sup>2</sup> (3.3.34 m <sup>2</sup> ) per carton 16 pieces per carton 52 cartons per pallet
<b>Tile Size</b>	18" x 18" (nom) / 457.2 mm x 457.2 mm		
<b>Overall Thickness</b>	0.12" / 20 mil		
<b>Wear Layer</b>	3 mm / 0.50 mm	<b>Weight Per Carton</b>	42.33 lbs / 19.20 kg
<b>Edge</b>	Square		
<b>Construction Material</b>	Solid Vinyl Plank (100% Virgin)		
<b>Finish</b>	UV Cured Polyurethane Coating		
<b>Warranty</b>	15 Year Commercial / 25 Year Residential Limited		

### Product Testing

Size and Squareness	ASTM F 2421	Passes
Residual Indentation	ASTM F 1914	Passes
Dimensional Stability	ASTM F 2199	Passes
Flexibility	ASTM F 137	Passes
Thickness	ASTM F 386	Passes
Abrasion Resistance	ASTM D 4060	Passes
Static Load Limit	ASTM F 970	Passes
Static Load Limit (Armstrong Modification)	ASTM F 970	Passes
Chemical Resistance	ASTM F 925	Passes
Smoke Density (Flaming)	ASTM E 662/NFPA 258	Passes
Smoke Density (Non-Flaming)	ASTM E 662/NFPA 258	Passes
Critical Radiant Flux	ASTM E 648/NFPA253/FTM372	Passes
Static Coefficient of Friction	ASTM C 1028 Meets 0.60	Passes
Indoor Air Quality	CA 1350 (CHPS)	Passes
Indoor Air Quality - Adhesives	FloorScore	
Certified Low Emitting Product	LEED EQ4.3	Meets Guidelines
Certified Low Emitting Adhesive	LEED EQ4.1	Meets Guidelines
Recyclability		100% Recyclable

## Chords<sup>TM</sup>

## 3mm Luxury Vinyl Plank

<b>General Testing Standard</b>	ASTM F-1700, Class III, Type B	<b>Packaging</b>	34.55 ft <sup>2</sup> (3.21 m <sup>2</sup> ) per carton 14 pieces per carton 55 cartons per pallet
<b>Plank Size</b>	7" x 48" (nom) / 187 mm x 1227 mm		
<b>Overall Thickness</b>	0.12" / 20 mil		
<b>Wear Layer</b>	3 mm / 0.50 mm	<b>Weight Per Carton</b>	41.77 lbs / 18.95 kg
<b>Edge</b>	Square		
<b>Construction Material</b>	Solid Vinyl Plank (100% Virgin)		
<b>Finish</b>	UV Cured Polyurethane Coating		
<b>Warranty</b>	15 Year Commercial / 25 Year Residential Limited		

### Product Testing

Size and Squareness	ASTM F 2421	Passes
Residual Indentation	ASTM F 1914	Passes
Dimensional Stability	ASTM F 2199	Passes
Flexibility	ASTM F 137	Passes
Thickness	ASTM F 386	Passes
Abrasion Resistance	ASTM D 4060	Passes
Static Load Limit	ASTM F 970	Passes
Static Load Limit (Armstrong Modification)	ASTM F 970	Passes
Chemical Resistance	ASTM F 925	Passes
Smoke Density (Flaming)	ASTM E 662/NFPA 258	Passes
Smoke Density (Non-Flaming)	ASTM E 662/NFPA 258	Passes
Critical Radiant Flux	ASTM E 648/NFPA253/FTM372	Passes
Static Coefficient of Friction	ASTM C 1028 Meets 0.60	Passes
Indoor Air Quality	CA 1350 (CHPS)	Passes
Indoor Air Quality - Adhesives	FloorScore	
Certified Low Emitting Product	LEED EQ4.3	Meets Guidelines
Certified Low Emitting Adhesive	LEED EQ4.1	Meets Guidelines
Recyclability		100% Recyclable